

AI NVR

The Artificial Intelligence (AI) Network Video Recorder (NVR) is a purpose-built security-hardened NVR, with built-in server-side analytics that unlocks Avigilon's advanced AI capabilities on any connected video stream. This cost-effective, plug-and-play appliance combines high-performance recording with video analytics in an easy-to-deploy turnkey solution. An IT-friendly solution, the AI NVR is built on a hardened embedded OS, which can be remotely managed with Avigilon Cloud Services (ACS). Avigilon regularly provides a single firmware package that not only updates the AI NVR, but also any connected cameras, and clients. Add the power of Avigilon's advanced neural-network-based analytics to your video streams with AI NVR.





Features



SERVER-SIDE ANALYTICS FOR NON-ANALYTIC CAMERAS

Bring Object Detection, Appearance Search, Face Recognition, and No Face Mask Detection to your existing non-analytic cameras

| - | - | 0 |
|---|---|---|
| | | |
| Ξ | - | 0 |

HIGH PERFORMANCE

Up to 1700mbps of total throughput, while simultaneously running analytics



REMOTE MANAGEMENT

Use ACS to manage multiple AI NVRs in a single building or globally from a central location



ENHANCED SECURITY

All Al NVRs run Avigilon Hardened OS on an encrypted solid state drive to minimize attack vectors



CLOUD REMOTE SITE UPDATE

Avigilon Al NVR, Cameras, and Clients can all be remotely upgraded together with a single signed and encrypted firmware package



SIMPLIFIED NETWORKING

Full recording throughput can be run on a single network port with additional ports used for failover



REMOTE NOTIFICATIONS ON MOBILE

Receive instant notifications to any mobile device with full support for remote alerts. Out-of-the-box built-in web endpoint technology optimizes the AI NVR for mobile connections



ALL-IN-ONE DEVICE

Achieve lower deployment costs with a single device that performs as an NVR and an analytics server

Analytics



Object Detection[™]

Detects and classifies people or vehicles to help operators verify and respond faster. Next-generation analytics provide improved object classification.

ACC7-VAC license required



Avigilon Appearance Search[™]

Quickly locates a specific person or vehicle of interest across an entire site using a sophisticated deep learning AI search engine.



Face Recognition

Detects matches from managed watchlists to alert operators of people of interest. Requires Appearance Search and an additional license.

ACC7-FACE license required



No Face Mask Detection

Determines whether a person is not wearing a face mask to help prevent community transmission.

ACC Enterprise required



ACC Enterprise required



Occupancy Counting

By placing cameras at exits and entrances, a running total of occupancy can be monitored in real time.

ACS Required

| | MAXIMUM SUPPORTED CAMERAS BY FEATURE ¹ | | | |
|-----------------|--|--|--|---|
| MODEL | OBJECT DETECTION ON NON-ANALYTICS CAMERAS ² | APPEARANCE SEARCH ONLY ³ | FACE RECOGNITION + APPEARANCE SEARCH ³ | FACE MASK DETECTION + APPEARANCE SEARCH ³ |
| AI NVR STANDARD | 10 | 200 | 100 | 200 |
| AI NVR VALUE | 5 | 200 | 50 | 200 |

¹ These performance figures are based on validation testing by Avigilon, using Avigilon Control Center software. For more information, contact Avigilon Sales.

48 TB

² For cameras at 2MP and 30 images per second (ips).

³ Requires H5A, H4A, or Classified Object Detection running on non-analytic cameras.

Specifications

AI NVR Standard

32 TB

24 TB



6 TB

12 TB

SYSTE

| SYSTEM Avigilon Contr Edition | | ol Center™ | Core, Standard, and Enterprise* compatible (ACC camera licenses are sold separately) | Core, Standard, and Enterprise* compatible (ACC camera licenses are sold separately) | |
|--|---|--------------------------------|--|---|--|
| Network Video Streaming Performance | Network | Network Connection | 1GbE Networking | 1GbE Networking | |
| | Video Streaming | Recording Rate ¹ | Up to 900 Mbps | Up to 900 Mbps | |
| | Performance | Playback Rate | Up to 800 Mbps | Up to 800 Mbps | |
| | Operating Syst | em | Avigilon Hardened OS, supports secure remote upgrades | Avigilon Hardened OS, supports secure remote upgrades | |
| | Drive | OS boot | 2 × M.2 Solid State drives, RAID 1 | 2 × M.2 Solid State drives, RAID 1 | |
| | Configuration | Video Data | RAID 6 — Up to 8 \times 3.5", hot-swappable | RAID 5 — 4 \times 3.5", hot-swappable | |
| | Recording Storage Capacity | | Up to 64 TB raw, 48 TB effective (RAID 6) | Up to 16 TB raw, 12 TB effective (RAID 5) | |
| | Network Interface | | 4 × 1 GbE RJ-45 ports (1000Base-T) | 2 × 1 GbE RJ-45 ports (1000Base-T) | |
| | Memory | | 2 × 8 GB | 2 × 8 GB | |
| | Processor | | Intel® Xeon® | Intel® Xeon® | |
| | Local Viewing | | No video outputs — Web-based administration only | No video outputs — Web-based administration only | |
| | Out-of-band Ma | anagement | iDRAC9 Express | iDRAC9 Express | |
| | Warranty | | 5-year Next Business Day (NBD) with onsite parts delivery service. 4-hour mission critical warranty upgrade available. | 5-year Next Business Day (NBD) with onsite parts delivery service. 4-hour mission critical warranty upgrade available. | |
| ELECTRICAL | Power Input | | 100 to 240 VAC, 50/60 Hz, auto-switching | 100 to 240 VAC, 50/60 Hz, auto-switching | |
| | Power Supply | | Single 1100W (80 PLUS Platinum), maximum 750 W (2559.1 BTU/h) — optional 2nd power supply available | Single 350W (80 PLUS Platinum), maximum 350 W (1340 BTU/ hr) — optional 2nd power supply available | |
| SUPPLIED ACCESSORIES | S Rack Rail System | | Sliding rail system with cable management arm. Supports: Tool-less mounting in 19"-wide EIA-310-E compliant square hole and unthreaded round-hole 4-post racks Tooled mounting in threaded hole 4-post racks | | |
| CERTIFICATIONS | IONS Certifications/Directives Safety Electromagnetic Emissions | | NDAA Compliant, TAA Compliant, UL, cUL, CE, RCM, BSMI, CCC, EAC, KC, NOM, NRCS, VCCI, RoHS, Reach (SVHC), WEEE, BIS | | |
| | | | UL/CSA/EN/IEC 62368-1 | | |
| | | | CFR Title 47, FCC Part 2, 15 Class A, ICES-003(A), EN 55032 Class A, EN 61000-3-2, EN 61000-3-3 | | |
| | Electromagneti | c Immunity | EN 55024 | | |
| | Energy | | Commission Regulation (EU) No. 617/2013 , ENERGY STAR 2.0 | | |
| | ROHS | | EN 50581:2012 | | |
| | test, 10 x 3MP non-ana | lytic cameras were run | 8 x 3MP-30fps cameras connected to a switch with a variable bit-rate per camera between 1 ning Classified Object Detection, Appearance Search, Face Recognition, and No Face Mask I playback traffic was run from the switch to the AI NVR over one CAT-5 cable connected to a s | Detection on the AI NVR Standard, while on AI NVR Value the same analytics were run on 5 x | |
| | | | OPERATING | STORAGE | |
| ENVIRONMENTAL | Temperature | | 10° C to 35° C (50° F to 95° F) | -40° C to 65° C (-40° F to 149° F) | |
| | Humidity | | 10% to 80% relative humidity with 29°C (84.2°F) maximum dew point | 5% to 95% RH with 33°C (91°F) maximum dew point. Atmosphere must be non-condensing at all times | |
| | Vibration | | 0.26 Grms at 5 Hz to 350 Hz | 1.88 Grms at 10 Hz to 500 Hz for 15 min | |
| | Shock | | One pulse on each side of the system of 71 G for up to 2 ms | Six consecutively executed shock pulses in the positive and negative x, y, and z axes (one pulse on each side of the system) of 71 G for up to 2 ms | |
| | Altitude | | 3,048 m (10,000 ft) | 12,000 m (39,370 ft) | |
| | | | | | |

Outline Dimensions

AI NVR Standard

Form Factor


2U rack mount chassis

Dimensions (LxWxH)


751 mm × 482.0 mm × 86.8 mm; 291⁄2" × 19" x 31⁄2"

Weight


34.5 kg (76 lbs)







AI NVR Value



Ordering Information

AI NVR Standard

| AINVR-STD-48TB | AI NVR Standard 48 TB (64 TB Raw) with Avigilon Control Center |
|--|--|
| AINVR-STD-32TB | AI NVR Standard 32 TB (48 TB Raw) with Avigilon Control Center |
| AINVR-STD-24TB | AI NVR Standard 24 TB (32 TB Raw) with Avigilon Control Center |
| Avigilan Control Center licenses must be nurchased senarately. Avigilan Appearance Search and facial recognition requires Enterprise version of the ACC software | |

AI NVR Value

| AINVR-VAL-12TB | AI NVR Value 12 TB (16 TB Raw) with Avigilon Control Center |
|---|--|
| AINVR-VAL-6TB | AI NVR Value 6 TB (8 TB Raw) with Avigilon Control Center |
| Avigilon Control Center licenses must be pure | hased separately. Avigilon Appearance Search and facial recognition requires Enterprise version of the ACC software. |

Software

| ACC7-ENT | ACC 7 Enterprise Edition license |
|---------------|---|
| ACC7-STD | ACC7 Standard Edition license |
| ACC7-COR | ACC7 Core Edition license |
| ACC7-VAC | ACC7 Video Analytics Channel license — Required for Classified Object Detection |
| ACC7-FACE | ACC7 Face feature channel license |
| ACC7-FACE-10C | ACC7 Face feature 10 channel license |

Accessories

| AINVR-STD-2NDPS | Redundant, hot-swappable power supply for AINVR-STD |
|-----------------------|---|
| AINVR-VAL-2NDPS | Redundant, hot-swappable power supply for AINVR-VAL |
| AINVR-HDD-HOT-8TB | Spare hard drive, 8TB, for AINVR STD 48TB/32TB |
| AINVR-HDD-HOT-4TB | Spare hard drive, 4TB, for AINVR STD 24TB, AINVR VAL 12TB |
| AINVR-HDD-HOT-2TB | Spare hard drive, 2TB, for AINVR VAL 6TB |
| IDRAC9-ENT-UPG | iDRAC Enterprise upgrade |
| AINVR-STD-WARR-5Y4HMC | 4-hour MC (mission critical response) service-level agreement upgrade for AINVR-STD |
| AINVR-VAL-WARR-5Y4HMC | 4-hour MC (mission critical response) service-level agreement upgrade for AINVR-VAL |
| AINVR-KYD-WARR-5YR | Keep Your Drive warranty for AINVR-STD and AINVR-VAL |

AI NVR-XXX-XXTB-NA =

(!!)





AI NVR-XXX-XXTB-**EU** =

 \odot





© 2020, Aviglion Corporation. All rights reserved. AVIGILON topo. AVIGILON APPEARANCE SEARCH, AVIGILON CONTROL CENTER, and ACC are trademarks of Aviglion Corporation Intel and Xeon are trademarks of Interportation or its subsidiaries in the U.S. and/or other countries. ONVIF is a trademark of Omir, Inc. Linux is the registered trademark of Linus Torvalds in the U.S. and other countries. NVIDIA and Quadro are registered trademarks of MVIDIA Corporation. Other names to logos mentioned may be the trademark of their respective owners. The absence of the symbols " and " in proximity to each trademark in this document or at all is not a disclaimer of ownership of the related trademark. Aviglion Corporation protects is innovations with patents issued in the United States of America and other jurisdictions worldwide (see <u>www.aviglion.com/about/ip</u>). Unless stated explicitly and in writing, no license is granted with respect to any copyright, industrial design, trademark, related or and related trademark in this document. The absence of the symbols " and " in proximity to each trademark in this document or at all is not a disclaimer of ownership of the related trademark. Aviglion Corporation protects is innovations with patents issued in the United States of America and other jurisdictions worldwide (see <u>www.aviglion.com/about/ip</u>). Unless stated explicitly and in writing, no license is granted with respect to any copyright, industrial design, trademark, related or trademark in this document.